

## TOLERANCES ON APERTURE WIDTHS FOR INDUSTRIAL WIRE CLOTH AND SCREENS

NOMINAL APERTURE SIZE  (1)	TOLERANCES IN AVERAGE APERTURE  (2)	MAXIMUM PERMISSIBLE VARIATION IN INDIVIDUAL APERTURE SIZE  (3)
125mm	± 3.8 mm	8 mm
Under 125 mm to 90 mm	± 3.5 mm	6.3 mm
Under 90 mm to 63 mm	± 2.54 mm	5 mm
Under 63 mm to 35.5 mm	± 1.9 mm	3.2 mm
Under 35.5 mm to 25 mm	± 1.14 mm	2.4 mm
Under 25 mm to 18 mm	± 0.76 mm	1.8 mm
Under 18 mm to 12.5 mm	± 0.51 mm	1.4 mm
Under 12.5 mm to 9 mm	± 0.43 mm	1.2 mm
Under 9 mm to 6.3 mm	± 0.38 mm	0.85 mm
Under 6.3 mm to 4.5 mm	± 0.30 mm	0.75 mm
Under 4.5 mm to 3.15 mm	± 0.25 mm	0.60 mm
Under 3.15 mm to 2.24 mm	± 0.18 mm	0.42 mm
Under 2.24 mm to 1.60 mm	± 0.13 mm	0.32 mm
Under 1.60 mm to 1.00 mm	± 88 μm	0.25 mm
Under 1.00 mm to 500 μm	± 54 μm	180 μm
Under 500 μm to 250 μm	± 27 μm	110 μm
Under 250 μm to 125 μm	± 14 μm	75 μm
Under 125 μm to 71 μm	± 8 μm	56 μm
Under 71 μm to 56 μm	± 6 μm	45 μm
Under 56 μm to 36 μm	± 5 μm	36 μm
Under 36 μm to 20 μm	± 4 μm	20 μm